

DPM 253

**MATERIAL SAFETY
DATA SHEET**



I. PRODUCT IDENTIFICATION

Product Name Form-A-Gasket® #3


Part No. 80017, -19

Product Type _____

Formula No. _____

II. COMPOSITION

Ingredients	% by Wt.	Hazard
Isopropyl Alcohol	20-25	Flammable
Modified Natural Resins	55-60	
Mineral Fillers	15-20	



III. CHEMICAL AND PHYSICAL PROPERTIES

Vapor Pressure _____

Specific Gravity ~ 1.1 @ R.T.

Vapor Density ~ 2

Boiling Point ~ 180°F

Solubility in Water Partial

pH _____

Appearance Dark Brown liquid

Odor Alcoholic

IV. TOXICITY AND HEALTH HAZARD DATA

Toxicity

TLV Isopropyl Alcohol = 400 ppm TWA

Symptoms of Overexposure

Vapor above TLV is irritating to eyes, nose, throat and
can cause headache, dizziness, nausea.

Emergency Treatment Procedures

Ingestion

Induce vomiting and get medical attention.

Inhalation

Remove to fresh air.

Skin Contact

Wash with soap and water.

Eye Contact

Flush with water and consult a physician

Personal Protection

Eyes

Safety glasses recommended

Skin

Ventilation

Must be adequate to avoid exceeding TLV

V. FLAMMABILITY AND EXPLOSIVE PROPERTIES

Flash Point

55°F

Method

Closed Cup

Explosive Limits (% by volume in air)

Lower 2 %Upper 12 %

Recommended Extinguishing Agents

CO₂, Dry Chemical Foam

Hazardous Products Formed by Fire or Thermal Decomposition

Standard for organic compounds

Unusual Fire or Explosion Hazards

None

Compressed Gases

Name None

Pressure at Room Temperature

VI. REACTIVITY DATA

Stability

☒ Stable☐ Unstable

Hazardous Polymerization

☐ May Occur☒ Will Not Occur

Hazardous Decomposition Products (non-thermal)

Incompatibility

Strong Oxidizer

V. SPILL OR LEAK AND DISPOSAL PROCEDURES

Steps to be taken in case of spill or leak Soak up in inert absorbent and
container until disposal. Scrape up as much as possible and store in a closed
Residues may be cleaned up with isopropyl alcohol.

Recommended methods of disposal

Landfill or incinerate following EPA and local regulations.

VIII. STORAGE AND HANDLING PROCEDURES

Storage

Store away from heat and flame.

Handling

Avoid prolonged breathing of vapors.

IX. SHIPPING REGULATIONS

Type or Class DOT ORM-D

IATA Class 3 - Flammable liquid

Proper Shipping Name DOT Consumer Commodity

IATA Resin Solution, flammable UN #1866

Prepared By Stephen Repetto

Title Environmental Health & Safety Specialist

Date September 21, 1983